Water-based preparation with a high-alkaline pH, manufactured on the basis of selected tensides with an addition of organic solvent

Is a very effective preparation for spot removal of new and old stains made by oil, greases and other petroleum-type substances.

Quickly and thoroughly removes new and old oil stains.
Preserves the original surface colour.

Application area

Parking lots, garages, driveways, sidewalks.
paving Stone
concrete
terrazzo
granite
marble
travertine
tiles
clinker
teracotta

Product can be use outdoor only.

The preparation is manufactured in a ready-to-use version.
Do not dilute.
DUE TO THE NATURE OF THE PRODUCT, BEFORE OPENING THE PACKAGE, SHAKE IT SEVERAL TIMES.

Application

Shake well before use.
Protect non-cleanable areas by using an oil-resistant material covers.
Apply the OL stain remover with a soft paintbrush, brush, etc. on the surface to be cleaned.
After application, the applied surface should be vigorously brushed with a paintbrush or brush for 5-10 seconds using circular motion.
Leave the preparation on the surface for about 2-3 minutes, do not let it dry out and brush the surface vigorously again.
After another 2-3 minutes, remove the reacted preparation and dirt with an absorbent material.
If the finished result is not totally satisfactory, repeat the product application process as described above 2-3 times
After completion of works, rinse the cleaned areas thoroughly with water.
Recommendations:
Before application, we recommend testing the product on a small, unexposed area.

Before cleaning, be sure to wear safety equipment such as protective googles and gloves.
Carry out the work in good light,
The OL preparation is not allowed to come into contact with materials which are not alkali-resistant.
It causes skin and eye irritation prolonged contact may cause damage to eyes/skin.

Do not apply during rain or frost and when surface and air temperature is < 10°C and > 30°C.

This information constitutes the basic guidelines for the use of the product and does not release from the obligation to perform work in accordance with the principles of art of the construction, conservation guidelines

and health and safety regulations.

Warnings

KEEP OUT OF REACH OF CHILDREN & PETS. ATTENTION CAUSTIC PRODUCT

The product contains: toluene; potassium hydroxide.

Technical specifications

Product density: approx. 1 kg/dm³
aqueous, colourless solution
pH: approx. 13
coverage: approx. 0.1-0.3 L / per 1 m2
characteristic scent, typical of solvents

Available packaging:

1L can

Expiry date:

Up to 36 months of storage at temperatures >+ 5°C to < 30°C, in original unopened manufacturer's packaging. Water-based product = it freezes at temperatures < 0°C.