ANTI-SLIP R-9 CERAMICS water-based product designed to reduce slip potential on wet floor surfaces by increasing the friction coefficient of treated areas without affecting the natural look of the floor.

The inorganic surface activators and polymers contained in the product, due to the chemical conversion reaction, produce permanent microstructures causing an increase in the kinetic friction coefficient.

This product can be used on both indoor and outdoor surfaces on old and new floors. Suitable for: Ceramics and porcelain tiles, clinker, natural porcelain glazed and polished tiles, terracotta, concrete, clinker, terrazzo, quarry tiler, ceramic and porcelain tiles as well on enamel bath/shower trays.

Application:

ANTI-SLIP R-9 CERAMICS is a ready to use product.

The product can be use applied with a hand sprayer, paint roller or brush.
Any adjacent surfaces not being treated with the product must be protected.
At the time of application the surface should be dry.
Apply during the coolest times of day.
Do not treat if the flooring is exposed to direct sunlight.
Apply at temperature between +10 and +25°C. Floor heating must be turned off before application of the product.
Apply the product generously and evenly on the entire area until the surface is saturated (no dry spot).
If applying on large area split it in two or more sections.
Gently agitate the surface with a deck brush of similar for approx. 1 min, until small bubbles appear.
Wait 2 minutes then brush the entire area once again to ensure the product is activated and evenly distributed on the entire surface at all times.
After 8 minutes remove the solution with a dry mop, cloth or wet wacuum cleaner.
Rinse the surface with clean water to stop the reaction.
Collect the water with a clean cloth, mop or wet vacuum cleaner and rinse the surface with water again.
In case the effect is unsatisfactory repeat the procedure.

After application of the product in accordance with the instructions, surface meets the safety requirements based on German standards DIN 51097, DIN 51130, DIN 51131.

Recommendations:

As surfaces may differ it is recommended to first make a test on a inconspicuous to actual application.

Wear protective goggles and nitril gloves when using the product
The product may irritate skin and eyes, it is necessary to ensure good ventilation of the room when applying product.
Do not mix with other products.
Do not dispose of the container after use, as it may cause environmental pollution.
Do not pour the product into drains or sewers.

This information constitutes the basic guidelines for the use of the product and does not release from the obligation to perform work in accordance with the principles of art of the construction, conservation guidelines and health and safety regulations.
Do not apply during rain or frost and when surface and air temperature is < 5°C and > 30°C.

Warnings:

KEEP OUT OF REACH OF CHILDREN & PETS. ATTENTION CAUSTIC PRODUCT

The product contains: alcohols, C12-15, ethoxylated; HF.

Technical specifications:

aqueous, colourless solution (slighty blue colour is permissible)
density approx. 1kg/dm3
pH 3, characteristic odour
coverage: 4-6 m2
durability of anti-slip effect: from 6 to 24 months

Available packaging: 1L/5L bottle

Expiry date: Up to 36 months of storage at temperatures >+ 5°C to < 30°C, in original unopened manufacturer's packaging. Water-based product = it freezes at temperatures < 0°C.